



POWERHOLD

COVE BASE ADHESIVE

Adhesivo para rodapié

DESCRIPTION:

Powerhold 5500 Cove Base Adhesive is a premium solvent-free adhesive with fast, aggressive wet suction to grip rubber and vinyl wall base. Powerhold 5500 can be used over most interior wall surfaces with the exception of vinyl wall covering and other similar non-porous surfaces that prevent the curing of any latex-based adhesive.

While the adhesive is designed to meet the challenges of poorly ventilated areas, sufficient air exchanges are still required to ensure proper curing of any latex-based adhesive.

Powerhold 5500 Adhesive is LEED compliant and is also compliant with South Coast Air Quality Management District Rule 1168.

DIRECTIONS:

1. Adhesive, wall base and job site must be conditioned at 65°F - 80°F for 48 hours before and after installation.
2. Use only on structurally sound surfaces, dry wall, concrete block, brick, plywood, paneling, masonry, plaster, etc.
3. Apply to surfaces that are clean, dry, and free from dust, wax and grease. Remove loose paint, plaster, old adhesive and other contaminants that would interfere with adhesion.
4. Cement or plaster must be thoroughly seasoned and dry.
5. With a 1/8" square or V-notched spreader, or proper width applicator nozzle, apply adhesive to the back of base or wall surface.
6. Press base firmly into place immediately after application of adhesive.
7. Roll base immediately after placement to the wall with a base roller to achieve adhesive transfer and the optimum bond.
8. For best results, it is recommended to wipe the back of rubber wall base with Mineral Spirits to remove residual mold release from manufacture.

DO NOT APPLY OVER NON-POROUS SURFACES SUCH AS MASONITE, PLASTIC LAMINATES, VINYL WALL COVERINGS OR METAL TOE KICKS.

RECOMMENDED SUBSTRATES:

- Porous Concrete
- Properly Prepared Gypsum
- APA Approved Plywood
- Drywall
- Fully Cured Porous Masonry Walls

RESTRICTIONS:

1. For interior installations only.
2. Do not install when ambient temperature is not between 60°F & 95°F.
3. Do not install when ambient relative humidity is above 65%.
4. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the user's intended use.

CLEAN-UP:

Remove wet adhesive immediately with a damp cloth. Dried adhesive residue will not be removed without damage to the substrate or wall base.

WARRANTY:

Powerhold offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical service at 800-832-9023 or visiting powerhold.com.





5500

TECHNICAL DATA:

Base Polymer:.....	Acrylic Polymer
Color:.....	Beige
Solids:.....	54-59%
VOC Content :.....	<5 grams per liter
pH:.....	9.3
Consistency:.....	Paste
Trowelability:.....	Light, Easy
Storage:.....	40°-95°F
Application Temperature:.....	65°-95°F (18°-35°C)
Open Time:.....	Up to 30 minutes
Freeze/Thaw Stability:.....	5 cycles @ 20°F


PACKAGING

- 4 Gallon (15.14 L) Black Plastic Pails
- 1 Gallon (3.79 L) Black Plastic Pails
- 30 Ounce (0.88 L) Cartridges

SHELF LIFE

One Year in Unopened Container

RECOMMENDED TROWEL SIZE AND COVERAGE:



Use a 1/8" x 1/8" x 1/8" square notch.
Approximately 180-215 linear feet
of 4" base per gallon



Use a 1/8" x 1/8" x 1/8" V-notch.
Approximately 175-195 linear feet
of 4" base per gallon



Use a 3" applicator nozzle
Approximately 45-60 linear feet
per 30 ounce cartridge



Use a 6" applicator nozzle
Approximately 40-55 linear feet
per 30 ounce cartridge