Printing Date 06/07/2013 Revision Number 1 Revision Date 06/07/2013

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Powerhold 525 Spray Contact Adhesive (Aerosol Can)
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Floor Covering Distributor Alliance 6320 Airport Freeway, Suite A Haltom City, TX 76117

- · Information department: Environment protection department.
- · Emergency telephone number: ChemTrec: UNITED STATES 1(800)424-9300 INTERNATIONAL 703-527-3887

2 Hazards identification

· Classification of the substance or mixture



GHS02 Flame

H224 Extremely flammable liquid and vapour.



GHS08 Health hazard

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.



GHS07

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Label elements
- GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07 GH

· Signal word Danger

· Hazard statements

Extremely flammable liquid and vapour.

(Contd. on page 2)

Printing Date 06/07/2013 Revision Number 1 Revision Date 06/07/2013

Trade name: Powerhold 525 Spray Contact Adhesive (Aerosol Can)

(Contd. of page 1)

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.


- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 4

Reactivity = 1

· HMIS-ratings (scale 0 - 4)



 *2 Health = *2

4 Fire = 4

PHYSICAL HAZARD 1 Physical Hazard = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
67-64-1	acetone	10-25%	
74-98-6	propane	10-25%	
110-54-3	n-hexane	5-20%	
115-10-6	dimethyl ether	5-20%	

4 First aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Printing Date 06/07/2013 Revision Number 1 Revision Date 06/07/2013

Trade name: Powerhold 525 Spray Contact Adhesive (Aerosol Can)

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Seek medical treatment.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, sand, extinguishing powder. Do not use water.

Use fire fighting measures that suit the environment.

· For safety reasons unsuitable extinguishing agents:

Water

Water and water with full jet

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Protective clothing and respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Open and handle receptacle with care.

Avoid prolonged or repeated contact with skin.

Avoid contact with eyes.

Wash thoroughly after handling.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.

(Contd. on page 4)

Printing Date 06/07/2013 Revision Number 1 Revision Date 06/07/2013

Trade name: Powerhold 525 Spray Contact Adhesive (Aerosol Can)

(Contd. of page 3)

· Information about storage in one common storage facility:

Store away from oxidizing agents.

Keep away from open flames and high temperatures.

- · Further information about storage conditions: Store receptacle in a well ventilated area.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

Conti	Control parameters				
· Comp	· Components with limit values that require monitoring at the workplace:				
67-64	-1 acetone (10-25%)				
PEL	2400 mg/m³, 1000 ppm				
REL	590 mg/m³, 250 ppm				
TLV	Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-475 mg/m³, (500) NIC-200 ppm BEI				
74-98	-6 propane (10-25%)				
PEL	1800 mg/m³, 1000 ppm				
REL	$1800 \text{ mg/m}^3, 1000 \text{ ppm}$				
TLV	Varies mg/m³, 1000 ppm				
110-5	4-3 n-hexane (5-20%)				
PEL	1800 mg/m³, 500 ppm				
REL	180 mg/m^3 , 50 ppm				
TLV	176 mg/m³, 50 ppm Skin; BEI				
115-1	0-6 dimethyl ether (5-20%)				
WEEL	. 1000 ppm				

· Ingredients with biological limit values:

67-64-1 acetone (10-25%)

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

110-54-3 n-hexane (5-20%)

BEI 0.4 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: 2.5-Hexanedione without hydrolysis

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Printing Date 06/07/2013 Revision Number 1 Revision Date 06/07/2013

Trade name: Powerhold 525 Spray Contact Adhesive (Aerosol Can)

(Contd. of page 4)

· Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses with side shields.



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties				
· Information on basic physical and · General Information	chemical properties			
· Appearance:				
Form:	Aerosol			
Color:	White			
· Odor:	Sweetish			
· Odour threshold:	Not determined.			
· pH-value:	Not determined.			
· Change in condition				
Melting point:	Undetermined.			
Boiling point:	-44 °C (-47 °F)			
· Flash point:	-97 °C (-143 °F)			
· Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:	235 °C (455 °F)			
· Decomposition temperature:	Not determined.			
· Auto igniting:	Product is not selfigniting.			
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.			
· Flammable limits:				
Lower:	1.2 Vol %			
Upper:	18.6 Vol %			

(Contd. on page 6)

Printing Date 06/07/2013 Revision Number 1 Revision Date 06/07/2013

Trade name: Powerhold 525 Spray Contact Adhesive (Aerosol Can)

	(Contd.	of page
· Vapor pressure at 20 °C (68 °F):	8300 hPa (6226 mm Hg)	
· Specific gravity at 20 °C (68 °F):	0.7 g/cm³ (5.842 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	75.5 %	
Solids content:	24.5 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions not reactive, as supplied.
- · Conditions to avoid

Heat, flames, sparks.

Exposure to high temperatures.

- · Incompatible materials: Reacts with oxidizing agents.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye:

Irritating effect.

Vapors may be severely irritating to the eyes.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

(Contd. on page 7)

Printing Date 06/07/2013 Revision Number 1 Revision Date 06/07/2013

Trade name: Powerhold 525 Spray Contact Adhesive (Aerosol Can)

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

· UN-Number · ADR, IMDG	Void	
· UN proper shipping name · ADR, IMDG	Void	
· Transport hazard class(es)		
· DOT, IATA		

· Class 2.1 • Label ORM-D

· ADR, IMDG

· Class Void

(Contd. on page 8)

Printing Date 06/07/2013 Revision Number 1 Revision Date 06/07/2013

Trade name: Powerhold 525 Spray Contact Adhesive (Aerosol Can)

Packing group
ADR, IMDG
Void

Environmental hazards:
Not applicable.

Special precautions for user
Not applicable.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
Not applicable.

UN "Model Regulation":
-

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

110-54-3 n-hexane

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· Cancerogenity categories

· Cancerogenuy categories	
· EPA (Environmental Protection Agency)	
67-64-1 acetone	I
110-54-3 n-hexane	II
· TLV (Threshold Limit Value established by ACGIH)	
67-64-1 acetone	A4
· MAK (German Maximum Workplace Concentration)	
None of the ingredients is listed.	
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	

· National regulations:

None of the ingredients is listed.

· Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 9)

Printing Date 06/07/2013 Revision Number 1 Revision Date 06/07/2013

Trade name: Powerhold 525 Spray Contact Adhesive (Aerosol Can)

(Contd. of page 8)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this MSDS [SDS] are presented in good faith and are believed to be correct as of the date of this MSDS [SDS], the supplier/manufacturer makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will the supplier/manufacturer be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the MSDS [SDS].

- · Department issuing MSDS: Environment protection department.
- · Creation Date: 06/07/2013
- · Abbreviations and acronyms:

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

USA