

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.**W. F. Taylor Co., Inc.**

11545 Pacific Avenue
Fontana, CA 92337-8228
951/360-6677
CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: **6600 Pressure Sensitive Adhesive**
ITEM NUMBER: PH6600-4
ITEM DESCRIPTION: PH6600 Pressure Sensitive Adh. 4-gal.
PRODUCT DESCRIPTION: Latex based adhesive
CHEMICAL FAMILY: Acrylic polymer, resin blend
REVISION DATE: 01/14/11
MANUFACTURED FOR: FLOOR COVERING DISTRIBUTOR ALLIANCE
ADDRESS: LAS VEGAS, NV
EMERGENCY PHONE NO: (800) 535 - 5053
TRADE NAME:

HMIS HAZARD RATING

LEAST: 0 HEALTH: 1
SLIGHT: 1 FLAMMABLE: 0
MODERATE: 2 REACTIVITY: 0
HIGH: 3
EXTREME: 4 PERSONAL PROTECTION: C

SECTION II HAZARDOUS INGREDIENTS

<u>COMPONENT/CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>% WT</u>	<u>NOTES</u>
NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS				

SECTION III PHYSICAL DATA

BOILING POINT: 212 Degrees F
LBS / GAL: 8.2 - 8.6
EVAPORATION RATE: Same as water
VAPOR DENSITY: Same as water
PERCENT VOLATILE: 45 - 49 (by weight)
COLOR: light yellow
ODOR: acrylic

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT, PENSKEY-MARTIN C.C.: NA
AUTO IGNITION TEMPERATURE, DEGREES F: NA
FLAMMABLE LIMITS IN AIR (% BY VOLUME): LEL: NA UEL: NA
EXTINGUISHING MEDIA:

(X) Water spray (X) Carbon dioxide () Other
(X) Foam (X) Dry chemical

SPECIAL FIRE FIGHTING PROCEDURES: Use self contained breathing apparatus.
UNUSUAL FIRE AND EXPLOSION HAZARDS: None known

PRODUCT NAME: **6600 Pressure Sensitive Adhesive**
ITEM NUMBER: PH6600-4
ITEM DESCRIPTION: PH6600 Pressure Sensitive Adh. 4-gal.
REVISION DATE: 01/14/11

SECTION V HEALTH HAZARD IDENTIFICATION

EFFECTS OF OVER EXPOSURE:

INHALATION: May cause respiratory irritation
EYES: May cause irritation
Skin: May cause irritation
Ingestion: May cause gastric disturbances

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with water for 15 minutes. Get medical attention.
SKIN: Wash with soap and water.
INHALATION: Move to fresh air. If unconcious, seek medical attention.
INGESTION: Contact physician at once. Do not induce vomiting.

SECTION VI REACTIVITY DATA

STABILITY: Stable
CONDITIONS TO AVOID: Protect from freezing.
INCOMPATIBILITY(MATERIALS TO AVOID): Oxidizing materials.
HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): Oxides of carbon, water, and organic compounds of unknown structure.
HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED

Keep out of sewer systems to prevent blockage due to polymer deposits. Use absorbent materials to collect and scrape up excess and place into closed DOT approved containers for disposal.

WASTE DISPOSAL: Abide by all State, Federal and local regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

VENTILATION AND ENGINEERING CONTROLS: Use local exhaust. Do not use closed air circulating system. Open windows and doors if necessary.
RESPIRATORY PROTECTION: NIOSH respirator if needed.
CLOTHING: chemical resistant gloves if desired to prevent contact.
EYE PROTECTION: chemical goggles
OTHER CLOTHING AND EQUIPMENT: If clothing is contaminated, remove and launder before rewearing.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTION FOR HANDLING AND STORING: Do not puncture container. Keep away from extreme heat and cold temperatures.
KEEP OUT OF THE REACH OF CHILDREN.
CAUTION: Do not take internally. If swallowed, DO NOT INDUCE VOMITING, CALL PHYSICIAN IMMEDIATELY.

SECTION X REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD(29CFR 1910.1200)HAZARD CLASS(ES): None
SARA TITLE III SECTION 312 HAZARD CLASS: None
EPA SARA TITLE III SECTION 313: None

CALIFORNIA PROPOSITION 65: This product contain a chemical(s) known to the state of California to cause cancer and/or reproductive harm.
