

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.****W. F. Taylor Co., Inc.**

11545 Pacific Avenue  
Fontana, CA 92337-8228  
951/360-6677  
CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: **7000 Wood Flooring Adhesive**  
ITEM NUMBER: PH7000-4  
ITEM DESCRIPTION: PH7000 Wood Flooring Adh 4-gal  
PRODUCT DESCRIPTION: Medium Viscosity Wood Adhesive  
CHEMICAL FAMILY: Amide-Ester-Acrylate Resin Blend  
REVISION DATE: 01/14/11  
MANUFACTURED FOR: FLOOR COVERING DISTRIBUTOR ALLIANCE  
ADDRESS: LAS VEGAS, NV  
EMERGENCY PHONE NO: (800) 535 - 5053  
TRADE NAME:

## HMIS HAZARD RATING

LEAST: 0 HEALTH: 0  
SLIGHT: 1 FLAMMABLE: 0  
MODERATE: 2 REACTIVITY: 0  
HIGH: 3  
EXTREME: 4 PERSONAL PROTECTION: C

**SECTION II HAZARDOUS INGREDIENTS**

<u>COMPONENT/CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>% WT</u>	<u>NOTES</u>
NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS				

**SECTION III PHYSICAL DATA**

BOILING POINT: No Data  
LBS / GAL: 9.6 - 10  
EVAPORATION RATE: low  
VAPOR DENSITY: low  
VAPOR PRESSURE: low  
PERCENT VOLATILE: 7 - 15 (By weight)  
COLOR: Beige  
ODOR: mild

**SECTION IV FIRE AND EXPLOSION HAZARD DATA**

DOT CATEGORY: not regulated  
FLASH POINT: none LEL: NA  
EXTINGUISHING MEDIA: none required  
UNUSUAL FIRE AND EXPLOSION HAZARDS: none  
SPECIAL FIRE FIGHTING PROCEDURES: none

**SECTION V HEALTH HAZARD IDENTIFICATION**

SYMPTOMS OF OVER EXPOSURE:  
INHALATION: May cause slight irritation to the upper respiratory tract.  
EYES: Vapor may cause irritation.  
SKIN: May cause slight skin irritation.  
INGESTION: Not a likely route of entry under proper handling conditions. May cause vomiting. Symptoms may be the same as inhalation.

HEALTH EFFECTS OR RISK FROM EXPOSURE:

---

PRODUCT NAME: **7000 Wood Flooring Adhesive**  
ITEM NUMBER: PH7000-4  
ITEM DESCRIPTION: PH7000 Wood Flooring Adh 4-gal  
REVISION DATE: 01/14/11

---

ACUTE: Inhalation may cause respiratory tract irritation. Contact with eyes and skin may result to irritation. Ingestion may result to gastric disturbances.

CHRONIC: Not known

FIRST AID PROCEDURES:

EYES CONTACT: Wash with running water for at least 15 minutes. If irritation persists, seek medical attention.

SKIN CONTACT: Remove from skin and wash with soap and water. If irritation persists, seek medical attention.

INHALATION: Move to fresh air. Administer oxygen, if necessary. Seek medical attention.

INGESTION: If swallowed, call physician.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known

---

**SECTION VI REACTIVITY DATA**

STABILITY: Stable

CONDITIONS TO AVOID: Protect from freezing, excessive heat.

INCOMPATIBILITY (MATERIALS TO AVOID): Metal salts may coagulate the product.

HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): Oxides of carbon, water, and organic compounds of unknown structure.

HAZARDOUS POLYMERIZATION: Will not occur.

---

**SECTION VII SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED

Keep out of sewer systems to prevent blockage due to polymer deposits. Use absorbent materials to collect and scrape up excess and place into closed DOT approved containers for disposal.

WASTE DISPOSAL: Abide by all State, Federal and local regulations.

---

**SECTION VIII SPECIAL PROTECTION INFORMATION**

VENTILATION AND ENGINEERING CONTROLS: Use local exhaust. Do not use closed air-circulating system. Open windows and doors if necessary.

RESPIRATORY PROTECTION: NIOSH respirator if needed.

CLOTHING: Chemical resistant gloves, apron, coveralls and boots as necessary to prevent contact.

EYE PROTECTION: Chemical goggles or face shield.

OTHER CLOTHING AND EQUIPMENT: If clothing becomes contaminated, remove and launder before re-wearing.

WORK PRACTICES, HYGIENIC PRACTICES: Follow label instructions.

OTHER HANDLING AND STORAGE REQUIREMENTS: Protect against physical damage. Store in cool, dry place (50-90F). Keep away from heat and freezing conditions.

---

**SECTION IX SPECIAL PRECAUTIONS**

PRECAUTION FOR HANDLING AND STORING: Do not puncture container. Keep away from extreme heat and cold temperatures.

KEEP OUT OF THE REACH OF CHILDREN.

CAUTION: Do not take internally. If swallowed, DO NOT INDUCE VOMITING, CALL PHYSICIAN IMMEDIATELY.

---

---

PRODUCT NAME: **7000 Wood Flooring Adhesive**  
ITEM NUMBER: PH7000-4  
ITEM DESCRIPTION: PH7000 Wood Flooring Adh 4-gal  
REVISION DATE: 01/14/11

---

**SECTION X TOXICOLOGICAL PROPERTIES**

Not known

---

**SECTION XI REGULATORY INFORMATION**

OSHA HAZARD COMMUNICATION STANDARD(29CFR 1910.1200)HAZARD CLASS(ES): None  
SARA TITLE III SECTION 312 HAZARD CLASS: None  
EPA SARA TITLE III SECTION 313: None

---