



LVT/UNIVERSAL SOUND CONTROL UNDERLAYMENT

**Application**

- RESIDENTIAL
- COMMERCIAL

**Approved for use under**

- LVT/LVP
- LAMINATE
- ENGINEERED WOOD
- HARDWOOD

**Dimensions and packaging**

- Roll Size: 200/sf
- Roll Width: 36"
- Roll Weight: 22/lbs
- Rolls/Pallet: 24
- Pallets/Truck: 48 double stacked

**Specifications +/- 10%**

- Material Composition: Rubber
- Thickness: 1.8mm
- Density: 25lb/ft<sup>3</sup>
- Compression Set: ASTM D 1055-97 (22h, 70C) – 16%
- Indentation: ASTM F1914 – 12%
- Smoke Density: ASTM A662 – Less Than 89 Max
- Flammability Test: ASTM D 2859(DOC FF 1-70) – Pass
- Thermal Resistance (R-Value): 0.205
- Antimicrobial Protection: Yes
- Indoor Air Quality: CRI Certified For Low Emitting Materials
- Installation Methods: Float, Double Glue, Single Glue, Nail down, Staple
- Warranty: Limited Lifetime

### **Approved Substrates**

- Completely Cured Concrete
- Interior Plywood
- Cement Backer Units
- Properly prepared OSB

### **Sound Ratings**

- |                                 |                |
|---------------------------------|----------------|
| - Luxury vinyl tiles and planks | IIC 73, STC 63 |
| - Laminate and Wood Products    | IIC 67, STC 63 |

### **Sustainability and LEED**

- |                           |                                |
|---------------------------|--------------------------------|
| - Content:                | 100% Virgin Latex Rubber       |
| - Recyclability:          | 100% Post Consumer             |
| - Certification:          | Green Label Plus               |
| - LEED Credit EQ 4.3:     | Low-Emitting Materials         |
| - LEED Credit MRc5.1,5.2: | Regional Content 20-30%        |
| - LEED Credit IEQp3:      | Minimum Acoustical performance |