

COVE BASE ADKESIVE

Pegamento bajo de la ensenada



DESCRIPTION:

POWERHOLD 5500 is a white acrylic cove base adhesive formulated for the installation of Rubber and Vinyl Cove Base over wood, concrete, brick, plaster, wallboard or other porous surfaces. Good wet suction for outside and inside corners. Will not contribute to staining, shrinkage or plasticizer migration.

PRIOR TO INSTALLATION:

Wall surfaces should be sound, dry, clean and porous. Remove vinyl or silicone treated wall covering and adhesives from the area that is to receive this adhesive. Roughen glossy surfaces such as enamel paint and rinse alkaline surfaces with vinegar or acetic acid. Cove base should be laid out flat, and the room, cove base and adhesive should be preconditioned at approximately 70 degrees F for 24 hours prior to and after installation. For best adhesion with molded rubber cove base, wipe the back of the base with damp cloth, prior to installation.

INSTALLATION INSTRUCTIONS:

Spread the adhesive on the Cove Base with 3/32" x 3/32" x 3/32" V-Notch trowel or cartridge gun, to leave an ample amount of adhesive for the wall surface. The Cove Base can be set in place up to 15 minutes after the adhesive is spread. Press firmly to the wall and rub or roll to get a smooth, even bond. Check to see that the adhesive has proper transfer to the wall. Clean-Up: Use warm soapy water while adhesive is still wet. When dry, POWERHOLD Cleaning Solvent.

CAUTION:

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.





TECHNICAL SPECIFICATIONS

For Product No.:5500

VOC's:Low

Base:Acrylic polymer blend

Color:White

Freeze Thaw Stability:Stable

Clean Up -

PACKAGING

4 Gallon (15.14L) Black Plastic Pails

SHELF LIFE

1 - Year when stored in original, unopened container

COVERAGES (APPROXIMATE)



Up to 160 sq. ft./gal. Up to 4.0 sq. meters/liter 2.4mm x 2.4mm x 2.4mm

Rubber and Vinyl Cove Base