



SAFETY DATA SHEET

1. Identification

Product identifier Powerhold 900P Primer

Other means of identification

SDS number 14000550005

Synonyms Surface primer, Sealer

Recommended use Interior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name Floor Covering Distributor Alliance

Address PO Box 7558
Ft. Worth, TX 76111

Telephone 1-844-874-3232 Technical Assistance

Website www.powerhold.com

Emergency phone number 1 (800) 507-8899

2. Hazard(s) identification

Physical hazards Not classified.

Health Hazards Sensitization, skin Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction. Very toxic to aquatic life.

Precautionary statement

Prevention Avoid breathing mist or vapor. Wear protective gloves. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Contaminated clothing should not be allowed out of the workplace.

Storage Store as indicated in Section 7.

Disposal Dispose of in accordance with local, state, and federal regulations.

Hazard(s) not otherwise classified (HNOC) None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Urea	57-13-6	< 5
5-Chloro-2-methyl-2H-isothiazol-3-one	26172-55-4	< 0.005

Composition comments All concentrations are in percent by weight unless ingredient is a gas.

4. First-aid measures

Inhalation	Exposure to mists may cause temporary irritation to eyes, skin, nose, throat, and upper respiratory tract. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.
Skin contact	Rinse area with plenty of water. Get medical attention if irritation develops and persists.
Eye contact	Do not rub eyes. Flush thoroughly with water. If burning, redness, itching, pain, or other symptoms develop or persist get medical attention.
Ingestion	Rinse mouth. Get medical attention if any discomfort occurs.
Most important symptoms/effects, acute and delayed	Under normal conditions of intended use, this product is not expected to be a health risk. Overexposure is highly unlikely at concentrations present in this product.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	Not applicable.
Specific hazards arising from the chemical	Not a fire hazard.
Special protective equipment and precautions for firefighters	Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use standard firefighting procedures and consider the hazards of other involved materials.
Specific methods	Cool material exposed to heat with water spray and remove it if no risk is involved.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	See Section 8 of the SDS for Personal Protective Equipment.
Methods and materials for containment and cleaning up	Prevent entry into confined areas or water systems. Dilute with water and mop or wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Dispose of waste according to local regulations.
Environmental precautions	Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling	Minimize exposure to mists. In case of insufficient ventilation, wear suitable respiratory equipment. Observe good industrial hygiene practices. Use proper lifting techniques.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry place. Store in a closed container away from incompatible materials, food, or drinking water. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Keep containers closed when not in use.

8. Exposure controls/personal protection

Occupational exposure limits

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
Urea (CAS 57-13-6)	TWA	10 mg/m3	Total particulate.

Biological limit values	No biological exposure limits noted for the ingredient(s).
Exposure guidelines	No exposure standards allocated.
Appropriate engineering controls	Provide sufficient ventilation for operations causing mist formation. Observe occupational exposure limits and minimize the risk of exposure.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear approved safety goggles.

Skin protection	
Hand protection	It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin contact use suitable protective gloves.
Other	Normal work clothing (long sleeved shirts and long pants) is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.
Thermal hazards	None.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Acrylic emulsion.
Color	White.
Odor	Slight acrylic.
Odor threshold	Not applicable.
pH	8.5 - 9.5
Melting point/freezing point	32 °F (0 °C)
Initial boiling point and boiling range	212 °F (100 °C)
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	1 - 1.2 (H ₂ O=1)
Solubility(ies)	
Solubility (water)	Soluble in water.
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.
Other information	
Bulk density	7.8 - 8.5 lb/gal
VOC (Weight %)	1.5 g/l

10. Stability and reactivity

Reactivity	Not available.
Chemical stability	Stable at normal conditions.

Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	None known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Spray mist may irritate the respiratory system.
Skin contact	May cause an allergic skin reaction after a single exposure. Prolonged or repeated skin contact may cause irritation and/or sensitization.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes and mucous membranes. Skin irritation.

Information on toxicological effects

Acute toxicity Low hazard for usual industrial or commercial handling by trained personnel.

Components	Species	Test Results
Urea (CAS 57-13-6)		
Acute		
<i>Oral</i>		
LD50	Rat	14300 mg/kg

Skin corrosion/irritation Prolonged or repeated skin contact may cause irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization	Not classified but possible due to skin sensitization effect.
Skin sensitization	May cause an allergic skin reaction after a single exposure or with repeated or prolonged skin contact.

Germ cell mutagenicity Not mutagenic in bacterial or mammalian systems.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Not a reproductive toxin.

Specific target organ toxicity - single exposure No data available, but none expected.

Specific target organ toxicity - repeated exposure No data available, but none expected.

Aspiration hazard Not classified.

Chronic effects No specific acute or chronic health impact noted.

12. Ecological information

Ecotoxicity Toxic to aquatic life.

Persistence and degradability Not persistent.

Bioaccumulative potential Bioaccumulation is not expected.

Partition coefficient n-octanol / water (log Kow)

Urea (CAS 57-13-6) -2.11

Mobility in soil The product is not mobile in soil.

Other adverse effects None expected.

13. Disposal considerations

Disposal instructions	Dispose waste and residues in accordance with applicable federal, state, and local regulations. Avoid discharge into water courses or onto the ground.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	Not regulated.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

5-Chloro-2-methyl-2H-isothiazol-3-one (CAS 26172-55-4) 1.0 % One-Time Export Notification only.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Not listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision**Issue date** 09-October-2014**Revision date** -**Version #** 01

Further information NFPA Ratings:
 Health: 2
 Flammability: 1
 Physical hazard: 0

NFPA Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Manufactured for Powerhold by United States Gypsum Company 550 West Adams Street Chicago, IL 60661.

Disclaimer This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.