POWERHOLD™

WARNING VERY SHARP BLADE | WEAR EYE PROTECTION PORTEZ DES LUNETTES DE PROTECTION | KEEP OUT OF REACH FROM CHILDREN

LAMINATE CUTTER USER GUIDE 9”/23 cm. *PH-809*

Read before use! Warning: failure to follow these rules may result in serious injury! Using this machine with respect and caution will considerably lessen the possibility of personal injury.

1. Read and understand this instruction manual before operating.
2. Stay alert. Do not operate while under the influence of drugs, alcohol, or medication.
3. Always wear safety approved eye protection with side shields.
4. Keep work area clean and free of debris.
5. Keep children and unauthorized persons away from the laminate cutter and the work area.
6. Make sure tool is secure. Operate only on a firm substrate or solid stand.
7. Use the right tool. Do not force the cutter or use it for a job for which it was not intended. This tool is designed to cut: residential grade/low-pressure laminate flooring, engineered wood flooring, vinyl composite tile, PVC tile, fiber cement board siding, vinyl siding, and pressboard lap siding. *see cut guide.
8. Keep blade sharp. A dull blade will not perform properly.
9. Always keep hands away from blade while operating or carrying.
10. Do not alter or misuse this tool. It is precision built; modifications not specified in this manual may result in a dangerous condition.
11. Maintain with care. Follow instructions for cleaning, lubricating and changing accessories.
12. Use only recommended accessories. The use of improper accessories may cause hazards or injury.
13. Never leave the cutter unattended. Secure the handle with the safety lock when not in use (see Making Cuts).
14. Warning: the dust generated by cutting certain wood, wood fiber and/or PVC products can be injurious to your health. The laminate cutter generally does not produce any dust; however, minimal creation of dust may be possible. Avoid ingesting any dust created through cutting.

In The Box:

Your laminate cutter comes ready to easily assemble*.



#	Name	Pcs.	Specifications	#	Name	Pcs.	Specifications
1	Plastic end cap	2		27	Worktable support	3	560.5*50*9
2	Guide sleeve	2	Ø30.08*188	28	Black cushion	2	18.5 x 15 x 35
3	Phillips screw			29	Worktable foot	1	9 x 50 x 382
4	Hexagon socket head cap screw	4	M6 x 60	30	Phillips screw	6	M6*35
5	Bolt	2	M10*70*34	31	Worktable	1	394*590
6	Hex. screw	8	M6*12	32	Phillips screw	14	M4 x 12
7	Spring washer	8	Ø6	33	Spring	1	Ø13 x Ø16 x 30 x 8
8	HSS blade	1	330*28	34	Spring cushion	1	20.5 x 20.5 x Ø11.5
9	Cam	6		35	Angle pointer	1	
10	Stop block	1	124*17.6*7.6	36	Steel ball	1	Ø8
11	Cam shaft	1	340*39*	37	Furniture nut	2	M6 x 8
12	Stop knob	1	M6*10*25*	38	Dial	1	160*87*1
13	Reinforce cam sleeve	1	46 x 50 x 25 x 25	39	Stop knob	1	M6*10*30*
14	Washer	5	Ø6 x Ø13	40	Black plastic slider	1	20 x 25 x 64
15	Hexagon socket head cap screw	2	M6 x 20	41	VØ5 Spring	1	
16	Square handle - outer	1	30 x 38 x 475	42	Ø3 x 18 Lock pin	1	
17	Phillips screw	2	M6*50	43	Phillips screw	6	Ø3 x 10
18	Phillips screw	4	M5*15	44	Square handle - inner	1	25 x 29 x 570
19	Guiding Rod	2	Ø20.06*50	45	Plastic sleeve	1	33 x 37 x 112
20	Spring	2	Ø2.5*10 Ø19*53	46	Handle knob	1	20.5 x 20.5 x Ø14 x 32
21	Upper Body	1	430*58*40	47	Push bar	1	Ø3 x 465
22	Phillips screw	4	Ø5 x 30		8mm Allen Key	1	8MML
23	Lower body	1	364*62*31		4mm Allen Key	1	4MML
24	Adjust plate	2	Ø58*16				
25	Phillips screw	4	M5*20				
26	Rubber foot	2	Ø32*5				

POWERHOLD™

WARNING VERY SHARP BLADE | WEAR EYE PROTECTION PORTEZ DES LUNETTES DE PROTECTION | KEEP OUT OF REACH FROM CHILDREN

LAMINATE CUTTER USER GUIDE 9”/23 cm. PH-809

Blade Adjustments

Honing the Blade:
Push the handle down until blade is 6mm / 1/4" open. Lay a flat face of the hone stone against the blade and slide from end to end 2 to 3 times. This removes the small burr formed when cutting hard products.

Blade Sharpening & Blade Replacement:
The blade can be sharpened several times before a replacement blade is necessary.

Cut Guide

CAUTION! USE HAND PROTECTION!
Your tool cuts a wide variety of products. Please refer to this cut guide for recommended products and thicknesses:

Laminate Flooring (direct pressure/residential grade	15mm or 9/16"
Engineered Wood	10mm or 3/8"
Parquet	12mm or 1/2"
PVC Tile	12mm or 1/2"
Vinyl Composite Tile	12mm or 1/2"
Rubber Tile	15mm or 9/16"
Carpet Tile	12mm or 1/2"
Soft Plastic	12mm or 1/2"
Leather	15mm or 9/16"
Cork	15mm or 9/16"
Wood Siding	15mm or 9/16"
Fiber Cement	15mm or 9/16"

Blade Adjustment Instructions:



1. Unscrew and remove the adjustment plate screws.



2. Tighten both adjustment plates by 1 or 2 holes. Note! The pitch on each lifting screw is 0.125mm. The adjustment on both plates must be the same.



3. Cut a piece of paper to ensure the tool is set correctly.

Making Cuts:

Caution! Ensure hand and eye protection are worn while operating



1. While gently pushing the handle down, slide safety lock in, then lift handle.

2. Place material to be cut on table. Bring handle down until blade touches material. Warning! Blade is very sharp. Keep fingers away from blade.

3. Push handle down completely to cut through material.

4. Safety lock should be put in the locked position after you finish the job.

Warning! Disabling reset function on safety lock is potentially hazardous.

Important!



After every 500 cuts, it is recommended that you lubricate the guiding sleeve with 10W-30 motor oil from top after removing the black caps. This will prevent premature wear-out of machine.