

## Suitable Substrates

Gypsum drywall, Plywood/OSB, Plaster, Concrete, Concrete Block, Cement backer board, Brick

## Cleanup

While wet, always apply soapy water to a clean cloth and wipe away adhesive. When material is dry, use denatured alcohol or appropriate adhesive remover. Do not pour directly onto flooring. Always check for compatibility on a piece of scrap flooring.

## Storage

Store unopened between 50-90°F. Shelf life is 2 years unopened. Do not allow product to freeze.

## Disclaimer

Users should determine the suitability of this information or product for their own purpose or application. The manufacturer is not responsible for the misuse of this product.

Not a dangerous substance or mixture according to OSHA 29 CFR 1910. 1200.

## First Aid Measures

**Eye contact:** Rinse immediately with plenty of water also under the eyelids, for at least 15 minutes. Do not rub affected areas. If eye irritation persists: Get medical advice/attention.

**Skin contact:** Wash off immediately with plenty of water for at least 15 minutes. In the case of skin irritation or allergic reactions see a physician. Inhalation: Remove victims to fresh air and keep at rest in a position comfortable for breathing.

**Ingestion:** Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Self-protection of the first aider: Use personal protective equipment as required.

## Disposal

Dispose of in accordance with local, regional, national, and international regulations as specified. Read SDS for detailed product information. SDS may be obtained by visiting the website.

**24-HOUR EMERGENCY CONTACT Chemtrec**  
(Transport/Environmental)  
1-800-424-9300 or 1-703-527-3887 (Outside U.S.)  
Rocky Mountain Poison Center: 1-866-767-5089



## UNIVERSAL COVE BASE ADHESIVE

### APPLICATIONS & COVERAGE

#### Cove Base

1/8" x 1/8" x 1/8" V Notch  
Up to 180 lf/gallon



1/8" x 1/8" x 1/8" V-notch

FOR PROFESSIONAL USE ONLY. NOT LABELED FOR CONSUMER USE.  
KEEP OUT OF REACH OF CHILDREN.

**1 US Gallon (3.79 L)**

## Instructions & Additional Info

For detailed installation guidelines, approved substrates, proper substrate preparation, technical data sheet, and safety data sheet, please see website.

### APPROVED PRODUCTS:

Vinyl Cove Base (PVC), Rubber Cove Base

### INSTALLATIONS:

**DISCLAIMER: FOLLOW THESE INSTRUCTIONS COMPLETELY OR DO NOT USE THIS PRODUCT.**

1. \*\*\* If unfamiliar with a product, always perform a bond test. Spread a small area of adhesive and install the desired product into the adhesive to ensure the desired bond is achieved. \*\*\*
2. After surface preparation, spread adhesive using the determined trowel as needed for desired product type.
3. After spreading the adhesive on the wall or cove base backing using the recommended application method, place base into the desired position on the wall and roll with a handheld roller.

**It is up to the end user to determine the proper application and coverage rate.**