



## APPROVED PRODUCTS

- Vinyl Cove Base (PVC)
- Rubber Cove Base

## SUITABLE SUBSTRATES

- Plywood/OSB
- Plaster
- Gypsum drywall
- Concrete
- Concrete Block
- Cement
- Brick

## TECHNICAL DATA

### For Product No.:

PH-5 Base

### Powerhold Trade Name:

Cove Base Adhesive

### VOC's:

Zero Calculated VOC's

### Base:

Acrylic Polymer

### Color:

Off-White

### Consistency:

Smooth, Easy Spreadability

### Open Time:

Up to 30 minutes

### Flammability:

Nonflammable

## PACKAGING

- 4 Gallon Black Plastic Pails
- 1 Gallon Black Plastic Pails
- 30 Ounce Cartridges

# PH-5

## Universal Cove Base Adhesive

### DESCRIPTION

Powerhold PH-5 Base Cove Base Adhesive is a very aggressive premium adhesive engineered with outstanding wet grab for the installation of a wide variety cove base. Powerhold PH-5 Base is solvent free and offers excellent performance characteristics complementing its strong and durable bond for challenging installations.

### COVERAGES

1/8" x 1/8" x 1/8" Saw Notch  
Up to 180 lf/gallon



3 Hole applicator  
Up to 60 lf/tube



### LIMITATIONS

- Not for exterior installations
- Not for use to encapsulate asbestos
- Ambient conditions must be between 50°-100° F – 20-75% RH
- Extreme ambient condition changes will affect the performance quality of the installation
- Do not install over chemically treated walls
- Do not allow product to freeze
- Do not use with dimensionally unstable wall base
- Determining the adhesive's suitability and compatibility for the intended use is the exclusive responsibility of the installer.

### SURFACE PREPARATION

**NOTE: FOLLOW ALL COVE BASE MANUFACTURERS GUIDELINES AS WELL AS THE FOLLOWING:**

- Wall must be dry, smooth, solid, structurally sound.
- Wall should be clean and free of dust, dirt, oil, grease, loosely bonded toppings, loose particles, and any other substance or condition that may prevent or reduce adhesion.
- Wall, adhesive and cove base must be acclimated with HVAC in operation for 48 hours prior, during, and continuously after installation is complete.
- Ambient temperature must be between 50°-100° F and relative humidity must be between 20-75% during and following wall base installation.

### INSTALLATION INSTRUCTIONS

Follow cove base manufacturer's guidelines for layout, design and any special precautions for installation.

**DISCLAIMER: FOLLOW THESE INSTRUCTIONS COMPLETELY OR DO NOT USE THIS PRODUCT.**

1) \*\*\* If unfamiliar with a product, always perform a bond test. Spread a small area of adhesive and install the desired product into the adhesive to ensure the proper bond is achieved. \*\*\*

2) After surface preparation, spread adhesive using the determined trowel as needed for desired product type. After spreading the adhesive on the wall or cove base backing using the recommended application method, place base into the desired position on the wall and roll with a handheld roller.

### CLEAN UP

- While wet, use a cloth and soapy water to remove wet adhesive
- When adhesive is dry, use denatured alcohol or appropriate adhesive remover
- Always check for compatibility on a piece of scrap product.

### STORAGE

- This product should be stored at temperatures between 50°-90° degrees F.
- This product has a shelf life of 2 years

www.powerhold.com/msds.com  
Technical Services: 1.800.832-9023