



Powerhold 115 Solvent Free Latex Carpet Pad Cement

POWERHOLD 115

DESCRIPTION:

Powerhold 115 is a solvent free, latex based adhesive which has been specially designed to bond carpet padding to a porous substrate prior to the installation of carpeting. PH 115 is a fast-setting adhesive which holds pad in place so carpet can be installed quickly. PH 115 is low odor, freeze-thaw stable, easy to pour and water resistant when dry.

DIRECTIONS:

1. Floor must be sound, clean and dry, free of dirt, wax dressings, grease, alkali or any foreign matter that would interfere with a good bond.
2. For best results, relative humidity should not exceed 65%.
3. Cut the pad to the proper length and determine layout of seams, etc. before spreading adhesive.
4. Apply beads of adhesive about 1/4" wide, 3" to 4" away from each wall, and in criss-cross pattern the full length of all pad seams. Hand pressure on side of container will help regulate flow.
5. Allow adhesive to set for 1 to 2 minutes, then install pad immediately.
6. Walk pad into adhesive, making certain to apply pressure at seam areas.
7. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the end user's intended use.

CLEAN-UP:

Remove wet adhesive immediately off tools, etc. using a soapy water solution. Use Mineral Spirits or Powerhold 050 Cleaner if adhesive is dry.

CAUTION: Mineral Spirits are flammable. Read and follow all precautions on container label.

PHYSICAL DESCRIPTION:

Weight/gallon	10.7
Consistency	Thin Pourable Liquid
Freeze Thaw	5 cycles @ +15°F
Shelf Life	One year @ 70°F in un-opened container

FOR MORE INFORMATION READ MATERIAL SAFETY DATA SHEET

KEEP OUT OF REACH OF CHILDREN

WARRANTY:

Powerhold offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical service at 844 638-4583(**GLUE**) or visiting www.powerhold.net.