



PRODUCT DATA SHEET

POWERHOLD FLOORSELL™ FLATBACK TAPE

Material Description: A kraft flatback paper tape with an aggressive pressure-sensitive, solvent cast natural/synthetic rubber adhesive is designed to offer a positive, attractive seal and excellent adhesion between FloorShell and X•Board seams. Also minimizes carton sealing failures and prevent pilferage. Designed for use in applications where reduced weight can provide packaging material savings. Approved as packaging tape by U.S. Postal Service and U.P.S. (United Parcel Service). Product is not repulpable.

Typical Applications: Great for seaming together FloorShell. Also: carton sealing, packaging, silk screening, picture framing, beaming/leasing, splicing, and tabbing.

Do not apply directly to floors.

Physical Properties

Backing	Kraft Flatback
Adhesive	Solvent Cast Natural / Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-101	58 (15.9 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	40 (175 N/25mm)
Elongation (% at break)	7
Total Thickness (mils) PSTC-133	7.3 (0.18mm)
Operating Temperature Range	
Operating	+40°F ~ +175°F (4.4°C ~ +79°C)
Color	Brown

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications

